

# Tyco Fire Products Dry Sprinkler Order Form 05-2007

Date: \_\_\_\_\_  
 Customer Name: \_\_\_\_\_  
 Ship-To Address: \_\_\_\_\_  
 \_\_\_\_\_  
 \_\_\_\_\_  
 PO Number: \_\_\_\_\_  
 Order Placed By: \_\_\_\_\_  
 Tag: \_\_\_\_\_

**Customer Service Use Only**

Order Number: \_\_\_\_\_  
 Customer Number: \_\_\_\_\_  
 Ship to Number: \_\_\_\_\_  
 ISR Initials: \_\_\_\_\_  
 Date/Time Entered: \_\_\_\_\_  
 Ack. Sent: \_\_\_\_\_  
 Freight Terms: \_\_\_\_\_

Tax Exempt # (If Applies) \_\_\_\_\_ \*\* must provide tax exempt certificate  
 Provide Quote Number for Special Pricing: \_\_\_\_\_  
 Special Instructions: \_\_\_\_\_

Please choose appropriate Part Number Configuration from Dry Sprinkler Configuration Worksheet and fill in below:

**PART #**    6 -  -  -  -  -

**Total Quantity:**

**Dry Head Desc:** \_\_\_\_\_    Escut Style: Std     Rec     Ext     No

\*\*please list length in inches

Quantity	Length

Quantity	Length

Quantity	Length

Quantity	Length

Dry Head Cover Plate Choices				
Finish	135 deg	Qty	165 deg	Qty
Natural Brass	567921135		567921165	
Bright Brass	567922135		567922165	
Bright Chrome	567929135		567929165	
Brushed Chrome	567928135		567928165	
Flat White	567920135		567920165	
Bright White	567924135		567924165	
Off White	567925135		567925165	
Black	567926135		567926165	
Special Order	56792X135		56792X165	

Refer to your tyco tech data for detailed product information

Dimension Listings		
DS-1:	DS-2:	DS-1 Ext Cov S/W:
STD - 2 1/2" - 48"	FLUSH - 2" - 48"	2 1/2" - 48"
REC - 3 1/2" - 48"	REC - 2 3/4" - 48"	<b>DS-C:</b>
DEEP Pend- 1/2" - 46"	EXT'D - 0" - 45 1/4"	5" - 48"
DEEP S/W - 1/2"-45 3/4"	NO ESCUT - 5"-48"	
UPRIGHT - 5" - 48"		
NO ESCUT - 5" - 48"		

Authorized Signature: \_\_\_\_\_ Date: \_\_\_\_\_

By signing above, Customer acknowledges that all specifications, measurements and other details with respect to Customer's dry sprinkler order are the sole responsibility of Customer. Customer agrees that it must ensure the accuracy of all such specifications, measurements and other details for each dry sprinkler order and that all requirements set forth in Tyco Fire and Building Products' applicable dry sprinkler Technical Data Sheet are complied with. Customer understands that dry sprinklers are being custom made pursuant to information supplied by Customer and that **under no circumstances are dry sprinklers returnable.**

# Tyco Fire Products Dry Sprinkler Configuration Worksheet

Choose series, style, temperature, & finish from charts and enter information on Dry Sprinkler Order Form

## DS-1

Series DS-1 Standard Coverage - STANDARD Response Pendent, Upright & Horizontal Sidewall		
PART NUMBER 60 - XX - X - X		
	TEMPERATURE	FINISH
96 PENDENT w/ STD Escutcheon	0 135° F / 57° C	1 BRASS / WHITE
93 PENDENT w/ DEEP Escutcheon	1 155° F / 68° C	4 WHITE / WHITE
97 PENDENT w/ STD Recessed Esc	2 175° F / 79° C	9 CHROME / CHROME
92 PENDENT w/o Escutcheon	3 200° F / 286° C	0 CHROME / WHITE
94 SIDEWALL w/ STD Escutcheon	4 286° F / 141° C	
53 SIDEWALL w/ DEEP Escutcheon	5 360° F / 182° C	
54 SIDEWALL w/o Escutcheon		
98 UPRIGHT w/o Escutcheon		

Series DS-1 Standard Coverage - QUICK Response Pendent, Upright & Horizontal Sidewall		
PART NUMBER 60 - XX - X - X		
	TEMPERATURE	FINISH
36 PENDENT w/ STD Escutcheon	0 135° F / 57° C	1 BRASS / WHITE
33 PENDENT w/ DEEP Escutcheon	1 155° F / 68° C	4 WHITE / WHITE
37 PENDENT w/ STD Recessed Esc	2 175° F / 79° C	9 CHROME / CHROME
32 PENDENT w/o Escutcheon	3 200° F / 286° C	0 CHROME / WHITE
34 SIDEWALL w/ STD Escutcheon	4 286° F / 141° C	
43 SIDEWALL w/ DEEP Escutcheon	5 360° F / 182° C	
44 SIDEWALL w/o Escutcheon		
38 UPRIGHT w/o Escutcheon		

Series DS-1 EXTENDED COVERAGE Horizontal Sidewall	
PART NUMBER 60 - XXX - X	
ORIENTATION / TEMPERATURE	FINISH
EC S / W QUICK RESPONSE - QR	1 BRASS / WHITE
350 135° F / 57° C	4 WHITE / WHITE
351 155° F / 68° C	9 CHROME / CHROME
EC S / W STANDARD RESP - SR	0 CHROME / WHITE
950 135° F / 57° C	
951 155° F / 68° C	

## DS-2

Series DS-2 Standard Coverage - STANDARD Response Pendent		
PART NUMBER 61 - XX - X - X		
	TEMPERATURE	FINISH
10 PENDENT w/ FLUSH Escutcheon	0 135° F / 57° C	1 BRASS / WHITE
11 PENDENT w/ STD Recessed Esc	1 155° F / 68° C	4 WHITE / WHITE
12 PENDENT w/ DEEP Escutcheon	2 175° F / 79° C	9 CHROME / CHROME
13 PENDENT w/o Escutcheon	3 200° F / 93° C	0 CHROME / WHITE
	4 286° F / 141° C	5 BRASS / BRASS
	* 286 N/A in Rec	

Series DS-2 Standard Coverage - QUICK Response Pendent		
PART NUMBER 61 - XX - X - X		
	TEMPERATURE	FINISH
30 PENDENT w/ FLUSH Escutcheon	0 135° F / 57° C	1 BRASS / WHITE
31 PENDENT w/ STD Recessed Esc	1 155° F / 68° C	4 WHITE / WHITE
32 PENDENT w/ DEEP Escutcheon	2 175° F / 79° C	9 CHROME / CHROME
35 PENDENT w/o Escutcheon	3 200° F / 93° C	0 CHROME / WHITE
	4 286° F / 141° C	5 BRASS / BRASS
	* 286 N/A in Rec	

Series DS-2 EXTENDED Coverage - QR & SR Response Pendent		
PART NUMBER 61 - XX - X - X		
	TEMPERATURE	FINISH
40 PENDENT w/ FLUSH Escutcheon	0 135° F / 57° C	1 BRASS / WHITE
41 PENDENT w/ STD Recessed Esc	1 155° F / 68° C	4 WHITE / WHITE
42 PENDENT w/ DEEP Escutcheon	2 175° F / 79° C	9 CHROME / CHROME
43 PENDENT w/o Escutcheon	3 200° F / 93° C	0 CHROME / WHITE
	4 286° F / 141° C	5 BRASS / BRASS
	* 286 N/A in Rec	

## DS-3

Series DS-3 EXTENDED COVERAGE STD Response Ordinary Hazard - Horizontal Sidewall (ECOH)	
PART NUMBER 61 - XXX - X	
ORIENTATION / TEMPERATURE	FINISH
FLUSH ESCUTCHEON	1 BRASS / BRASS
161 155° F / 68° C	4 WHITE / WHITE
163 200° F / 93° C	9 CHROME / CHROME
EXTENDED ESCUTCHEON	0 CHROME / WHITE
171 155° F / 68° C	
173 200° F / 93° C	
WITHOUT ESCUTCHEON	
151 155° F / 68° C	
153 200° F / 93° C	

## DS-C

Series DS-C Dry Concealed	
PART NUMBER 60-XXX-1	
STANDARD RESPONSE	X
60 - 86 X - 1	TEMPERATURE
QUICK RESPONSE	1 155° F / 68° C
60 - 46 X - 1	3 200° F / 93° C
EXT COVERAGE - QR	
60 - 45 X - 1	

## COVER PLATES

FINISH	135 DEG	165 DEG
Natural Brass	567 921 135	567 921 165
Bright Brass	567 922 135	567 922 165
Bright Chrome	567 929 135	567 929 165
Brushed Chrome	567 928 135	567 928 165
Flat White	567 920 135	567 920 165
Bright White	567 924 135	567 924 165
Off White	567 925 135	567 925 165
Black	567 926 135	567 926 165
Special Order	567 92X 135	567 92X 165

**REMINDER:**

135 Degree plates go with 155 heads

and

165 degree plates go with 200 degree heads

## DIMENSION MINIMUM & MAXIMUMS

DS-1		
STD Esc	2 1/2"	- 48"
REC Esc	3 1/2"	- 48"
DEEP Pend	1/2"	- 46"
DEEP S / W	1/2"	- 45 3/4"
UPRIGHT	5"	- 48"
NO Esc	5"	- 48"
EXT Cov S/W	2 1/2"	- 48"

DS-2		
FLUSH	2"	- 48"
REC Esc	2 3/4"	- 48"
DEEP Pend	0"	- 45 1/4"
NO Esc	5"	- 48"

DS-3		
FLUSH	2 1/4"	- 45 1/4"
DEEP Pend	1"	- 44"
NO Esc	5"	- 48"

DS-C		
FLUSH	5"	- 48"